

Insulating Bushes - Adjustable


Adjusts to accept various diameters and shapes • Locks quickly into panel thicknesses 0.8 - 3.2mm

Closes entry hole to insects and vermin

Resilient multiple supports absorb shock and vibration

Part Number	Panel Hole Diameter	Max. Cable Diameter A	Overall Length C	Outside Diameter B
22-PAB16	15.9	11.1	10.3	18.2
22-PAB19	19.0	12.7	9.9	21.8
22-PAB22	22.2	14.2	11.5	23.8
22-PAB25	25.4	19.0	11.5	26.9
22-PAB28	27.8	20.6	11.5	29.3

Material: Black Nylon 6/6 UL94V2



Open/Close Bushing



Protect wire, cable, tubing and hose from sharp, uneven drilled or punched holes

For 0.8mm to 3.2mm chassis thickness

Finger-tip pressure to install, no tool required. Can be applied after power cable was installed.

Part Number	Panel Hole Diameter A	Max. Cable Diameter B	Overall Diameter C	Overall Width L
22-POB09	9.5	6.7	12.2	10.3
22-POB13	12.7	8.0	15.4	10.3
22-POB16	15.8	11.5	18.7	10.3
22-POB19	19.0	13.1	20.1	10.3
22-POB22	22.2	17.0	24.8	10.3
22-POB25	25.4	20.2	28.0	10.3

Material: Black Nylon 6/6




Vent Plug - Locking

Positively snaps into panel thicknesses from 0.8mm to 3.2mm

Part Number	Panel Hole Diameter	Max. Panel Thickness	Head Dia. B	Depth C
22-PLV19B	19.1	3.2	23.0	10.3
22-PLV22B	22.5	3.2	25.8	11.5
22-PLV25B	25.4	3.2	30.5	11.5
22-PLV25W	25.4	3.2	30.5	11.5

Material: Black Heat Stabilised Nylon - UV Resistant - UL94V2

W = White



Window Plugs

Flat headstyle to minimise visual distortion

• Multiple locks 0.8mm to 3.2mm

Part Number	Panel Hole Diameter	Max. Panel Thickness	Head Dia. B	Depth C
22-PLW06	6.4	1.6	8.0	8.0
22-PLW10	9.5	3.2*	12.0	10.3
22-PLW13	12.7	3.2*	14.6	10.3
22-PLW16	15.9	3.2*	18.2	10.3

Material: Clear Copolyester

